

STILE BAROCCO VENEXIAN

Glossy effect decorative Stucco Veneziano

DESCRIPTION

VENEXIAN is a decorative acrylic stucco ideal for reproducing the ancient craft of the shiny Venetian stucco finish.

Venexian brings back to life and ancient effect, ideal this time for all types of environment and furnishing.

APPLICATION

- Make sure the surface is completely dry . If the surface is plastered, make sure it had a curing time of at least 28 days , depending on temperature.
- Make sure that the media has been well prepared and is suitable for coating: plaster must be dry, not have any granules , on old walls, make sure that there is no poor quality or powdery paint, remove flaking paint etc. .
- Apply 1 coat of SCIK PURAL ACRIL primer if necessary.
- Apply with a brush or roller one or two coats of DECOR FONDO PRIMER diluted with 5-10 % water.
- Apply the first coat of VENEXIAN colored by Tinting Machine. Use a stainless steel trowel, taking care to smooth the entire surface.
- Sand with very fine sandpaper any imperfections and brush off the dust.
- Once dry, apply a second coat of VENEXIAN creating the typical effects of a lime slate. Therefore you can get the effects of shiny marble , overlapping effects and so on....

OPTIONAL

- Apply CERA D'ARTE NEUTRA using a stainless steel trowel and spread the product over the entire surface.
- After 6-12 hours smooth the surface using a cloth


DECORAZIONI RIVEDIL S.r.l.

Via Prov.le per Veglie Km 0,500 - 73015 Salice Salentino (Le) Italy

Tel. (+39) 0832 731293 - (+39) 0832 731273

P.IVA 03937370751

www.rivedil.com - export@rivedil.com

TECHNICAL DATA	
Nature of the bond	Mineral and acrylic resins
Viscosity	
Drying Time	2 h at touch, 12 h complete.
Thinning	Ready to use
Yield	1,8-2,2m ² /Kg
Specific weight	1,500Kg/Lt
Colors	Bianco
Dry aspect	Polished marble effect
Wet aspect	Pasty white
Storing	Max Temp. +30°C, Min T. +5°C
Stability	2 years (in sealed, unopened original packing)
VOC	10µGr/m ³
TVOC	25µGr/m ³
PH	7-8°C
Cleaning	Water and Soap
Packing	5KG,20KG
CHARACTERISICS	
Characteristics:	Washable,Environmentally friendly.
Can be applied on:	Walls,Wood.
for:	Interiors/Exteriors.
Certifications:	
TOOLS AND RELATED PRODUCTS	
Tools:	Stainless Steel Trowel 200x80cm,Stainless Steel Trowel 240x100cm,.
Related products:	DECOR FONDO,CERA D´ARTE NEUTRA,HYDROCERA NEUTRA.

NOTES

- Please note that due to technical reasons caused by the tinting of the product the indicated Specific Weight of the product may differ from the Package Net Weight.
- In the original, sealed containers and in appropriate temperature conditions . The period of stability is purely indicative, and refers to the minimum stability period of the product if stored ideal conditions according to the instructions provided. If properly stored the products stability period may extend several years.
- Rivedil ensures that the information herein is provided to the best of its experience and its technical and scientific knowledge , however , being elements such as weather conditions, labor , tools, quality of third party products and others, not under the direct control of the Rivedil , this document does not constitute a warranty , nor does Rivedil authorize its agents and / or representatives to provide any kind of warranty based on the information contained in this document . We recommend that you always check the suitability of the product to each specific instance . This supersedes all previous editions.

DECORAZIONI RIVEDIL S.r.l.

Via Prov.le per Veglie Km 0,500 - 73015 Salice Salentino (Le) Italy

Tel. (+39) 0832 731293 - (+39) 0832 731273

P.IVA 03937370751

www.rivedil.com - export@rivedil.com